

CUSTOMER		
Customer name:		Computer article code:
Account Nr:	Offer or Order date:	Brochure product Number:

CUSTOMER DOCUMENTS		
Drawing:	Specifications:	
Data sheet:	Other:	

GENERAL SPECIFICATIONS (Optional information)		Cf. customer doc. <input type="checkbox"/>
Inside access <input style="width: 100%;" type="text"/>	Height & frame thickness <input style="width: 100%;" type="text"/> mm	
Outward opening <input type="checkbox"/>	Horizontal (Hinge pin large axis) <input type="checkbox"/>	Vertical (Hinge pin small axis) <input type="checkbox"/>
Autoclave <input type="checkbox"/>	Left opening <input type="checkbox"/>	Right opening <input type="checkbox"/>

MATERIAL (Compulsory information)		Customer doc. <input type="checkbox"/>
According to EN 10088-3 & EN 10028-7	Material marquing :	yes <input type="checkbox"/> no <input type="checkbox"/>
EN 1.4307- AISI 304 L <input type="checkbox"/>	EN 1.4404 - AISI 316 L <input type="checkbox"/>	Cert 3.1 B <input type="checkbox"/>
EN 1.4301- AISI 304 <input type="checkbox"/>	EN 1.4404 - AISI 316 <input type="checkbox"/>	Other <input style="width: 100%;" type="text"/>

SERVICE CONDITIONS (Compulsory information )			Customer doc. <input type="checkbox"/>
Fluid <input style="width: 100%;" type="text"/>	Max.Pressure Allowed <input style="width: 100%;" type="text"/> bar	Working Temp° <input style="width: 100%;" type="text"/> °C	
Density <input style="width: 100%;" type="text"/>	Absolute vaccum <input style="width: 100%;" type="text"/> bar	Max. Temp ° <input style="width: 100%;" type="text"/> °C	
Proposed Cleaning Device <input style="width: 100%;" type="text"/>	CIP / SIP <input style="width: 100%;" type="text"/>	Temp <input style="width: 100%;" type="text"/> °C	

CONSTRUCTION STANDARD (Compulsory information – pressure manholes)		Customer doc. <input type="checkbox"/>
Without PED <input type="checkbox"/>	PED Direct. 97/23/CE <input type="checkbox"/>	ASME VIII div. 1with U stamp <input type="checkbox"/>
CODAP 2005 (coef. 0.70) <input type="checkbox"/>	AD-Merkblatt <input type="checkbox"/>	ASME without U stamp <input type="checkbox"/>
CODAP 2005 (coef. 0.85) <input type="checkbox"/>	Dye penetrant test <input type="checkbox"/>	ASME CNR with U stamp <input type="checkbox"/>
Category 1/2/3/4 <input type="checkbox"/>	X ray picture <input type="checkbox"/>	ASME CNR without U stamp <input type="checkbox"/>
Additional Documentation:-		

GASKET QUALITY (Compulsory informations)		Customer doc. <input type="checkbox"/>
Butyl <input type="checkbox"/>	Neoprene <input type="checkbox"/>	Silicone-USP/Pharma <input type="checkbox"/> With certificate
EPDM <input type="checkbox"/>	Nitril (NBR) <input type="checkbox"/>	Aflas <input type="checkbox"/>
EPDM-E1 <input type="checkbox"/>	Silicone (standard one) <input type="checkbox"/>	F.S.I. <input type="checkbox"/>
FEP-Silicone <input type="checkbox"/>	Silicone - High T° <input type="checkbox"/>	Others <input style="width: 100%;" type="text"/>
FEP-Viton ® <input type="checkbox"/>	Silicone for water steam <input type="checkbox"/>	
Natural <input type="checkbox"/>	Viton ® (FPM) <input type="checkbox"/>	FDA cert. ? Yes <input type="checkbox"/> No <input type="checkbox"/>

<b>OPTIONS</b> (Compulsory information)	Customer doc. encl <input type="checkbox"/>
---	---

<b>SIGHT GLASSES:</b>	DIN 11851(scwd) <input style="width: 100%;" type="text"/>	DIN 28120 (flanged) <input style="width: 100%;" type="text"/>	
<b>Glass:</b>	Borosilicate <input type="checkbox"/>	Sodium silicate <input type="checkbox"/>	Contact gasket <input type="checkbox"/>
	Safety screen <input type="checkbox"/>	Wiper <input type="checkbox"/>	Glass cleaning pipe <input type="checkbox"/>
	Glass certificate 2.2 <input type="checkbox"/>	Glass test certificate <input type="checkbox"/>	
<b>Light:</b>	<input style="width: 50%;" type="text"/> Watts	<input style="width: 50%;" type="text"/> volts	ATEX <input type="checkbox"/> Push Button <input type="checkbox"/>

<b>ADDITIONAL SAFETY ITEMS OR OPENING ASSIST ON MANLIDS</b>		
Cover opening stop <input type="checkbox"/>	Eyebolt opening stop <input type="checkbox"/>	Cover spring or gaz spring assist <input type="checkbox"/>
Safety screen <input type="checkbox"/>	SYDEC ® Two-stage opening <input type="checkbox"/>	

**Notes**

<b>FINISHES</b> (Compulsory information)	Customer doc. <input type="checkbox"/>
--	--

<b>INSIDE</b>	Ra <= 0,2 / 0,4 / 0,6 / 0,8 / 1,0 / 1,6 µm	Other Ra :           µm
	Raw <input type="checkbox"/>	Pickled <input type="checkbox"/> Electropolished <input type="checkbox"/>
	Or Gritt : 60 / 120 / 180 / 240 / 320 / 400	Other gritt :

<b>OUTSIDE</b>	<b>WELDS GROUND TO RT 1,6 µm ?</b> <input type="checkbox"/> Yes <input type="checkbox"/> No	
	Ra <= 0,2 / 0,4 / 0,6 / 0,8 / 1,0 / 1,6 µm	Other Ra :           µm
	Pickled <input type="checkbox"/> Electropolished <input type="checkbox"/>	Bead blasted <input type="checkbox"/>
	Or Gritt : 60 / 120 / 180 / 240 / 320 / 400	Other gritt :

<b>GIVEN TO DESIGN OFFICE</b>		Signature - Sales
NO <input type="checkbox"/>	YES <input type="checkbox"/>	on the (date):

<b>ANSWER FROM THE DESIGN OFFICE</b>		Signature - Design office
<b>Feasibility :</b>	NO <input type="checkbox"/>	YES <input type="checkbox"/>
	NEW ARTICLE CODE :	
<b>Answer to the commercial (date) :</b>		

<b>CONTRACT REVIEW</b>		Signature - Technical
<b>Offer N° :</b>	<b>Answer to the customer (date) :</b>	